

RIMS AND BIAS TIRES

	RIMS/WHEELS	LBS	SIZE	
2	8" 4 Hole Silver		8X3.75 4-4	
3	8" 5 Hole Silver		8X3.75 5-4.5	
4	10" 4 Hole White		10X6 4-4	
5	10" 5 Hole White		10X6 4-4.5	
	<b>WHITE SPOKE</b>			
15	12" 4 Hole	1100	12X4 4-4	
16	12" 5 Hole	1100	12X4 5-4.5	
18	13" 5 Hole	1468	13X4.5 5-4.5	
20	14" 5 Hole	1870	14X6 5-4.5	
22	15" 5 Hole	2600	15X6 5-4.5	
23	15" 5 Hole MOD 5" WIDE	1870	15X5 5-4.5	
24	15" 6 Hole	2600	15X6 6-5.5	
25	16" 8 Hole	3750	16X6 8-6.5	
	<b>GALVANIZED SOLID</b>			
30	8" 4 Hole	1075	8X3.75 4-4	
31	8" 5 Hole	1075	8X3.75 5-4.5	
32	10" 4 Hole		10X6 4-4	
33	10" 5 Hole		10X6 5-4.5	
	<b>GALVANIZED SPOKE</b>			
35	12" 4 Hole	1100	12X4 4-4	
36	12" 5 Hole	1100	12X4 5-4.5	
37	13" 4 Hole	1468	13X4.5 4-4	
38	13" 5 Hole	1468	13X4.5 5-4.5	
39	14" 5 Hole	1870	14X6 5-4.5	
40	15" 5 Hole	2600	15X6 5-4.5	
41	15" 6 Hole	2600	15X6 6-5.5	
43	16" 6 Hole		16X6 6-5.5	
43G	16" 8 Hole		16X6 8-6.5	
	<b>BIAS</b>	<b>LOAD RANGE</b>	<b>PSI</b>	<b>WGT</b>
48	480 x 8	B	60	590
49	570 x 8	C	75	910
50	20.5 x 8.0 - 10	C	50	1105
51	20.5 x 8.0 - 10	E	90	1535
52	480 x 12	B	60	780
53	530 x 12	C	80	1045
55	ST175/80D13	C	50	1360
56	ST205/75D14	C	50	1760
56a	ST215/75D14	C	50	1870
57	ST205/75D15	C	50	1820
58	ST225/75D15	D	65	2540

RIMS AND BIAS TIRES

--	--	--	--	--	--