

RIMS AND BIAS TIRES

	RIMS/WHEELS		LBS	SIZE	
2	8" 4 Hole	Silver		8X3.75 4-4	
3	8" 5 Hole	Silver		8X3.75 5-4.5	
4	10" 4 Hole	White		10X6 4-4	
5	10" 5 Hole	White		10X6 4-4.5	
	WHITE SPOKE				
15	12" 4 Hole		1100	12X4 4-4	
16	12" 5 Hole		1100	12X4 5-4.5	
18	13" 5 Hole		1468	13X4.5 5-4.5	
20	14" 5 Hole		1870	14X6 5-4.5	
22	15" 5 Hole		2600	15X6 5-4.5	
23	15" 5 Hole	MOD 5" WIDE	1870	15X5 5-4.5	
24	15" 6 Hole		2600	15X6 6-5.5	
25	16" 8 Hole		3750	16X6 8-6.5	
	GALVANIZED SOLID				
30	8" 4 Hole		1075	8X3.75 4-4	
31	8" 5 Hole		1075	8X3.75 5-4.5	
32	10" 4 Hole			10X6 4-4	
33	10" 5 Hole			10X6 5-4.5	
	GALVANIZED SPOKE				
35	12" 4 Hole		1100	12X4 4-4	
36	12" 5 Hole		1100	12X4 5-4.5	
37	13" 4 Hole		1468	13X4.5 4-4	
38	13" 5 Hole		1468	13X4.5 5-4.5	
39	14" 5 Hole		1870	14X6 5-4.5	
40	15" 5 Hole		2600	15X6 5-4.5	
41	15" 6 Hole		2600	15X6 6-5.5	
43	16" 6 Hole			16X6 6-5.5	
43G	16" 8 Hole			16X6 8-6.5	
	BIAS		LOAD RANGE	PSI	WGT
48	480 x 8		B	60	590
49	570 x 8		C	75	910
50	20.5 x 8.0 - 10		C	50	1105
51	20.5 x 8.0 - 10		E	90	1535
52	480 x 12		B	60	780
53	530 x 12		C	80	1045
55	ST175/80D13		C	50	1360
56	ST205/75D14		C	50	1760
56a	ST215/75D14		C	50	1870
57	ST205/75D15		C	50	1820
58	ST225/75D15		D	65	2540

RIMS AND BIAS TIRES

--	--	--	--	--	--